






X. SMB: TRV.0480



X. SMB: TRV.0870




X. SMB: TRV.0860



X. SMB: TRV.0830



X. SMB: TRV.0680



X. SMB: TRV.0780



X. SMB: TRV.0070




X. SMB: TRV.0820




X. SMB: TRV.0790



X. SMB: TRV.0110



X. SMB: TRV.0810



X. SMB: TRV.0390




X. SMB: TRV.0410



X. SMB: TRV.0380




X. SMB: TRV.0420



X. SMB: TRV.0230



X. SMB: TRV.0430




X. SMB: TRV.0250



X. SMB: TRV.0440



Traviata





Traviata

Secondary Backing

Rugtype • Envers
Rücken • Sottotondo • Verso

SMB

Manufacturing process

Fabricagemethode • Technique de fabrication
Herstellungsort • Tecnica di fabbricazione • Técnica de fabricación

5/64" TWIST

Pile composition

Poolsamenstelling • Nature du velours
Polmaterial • Composizione felpa • Composición de pelo

PA

Primary backing

Tuftdoek • Premier dossier
Trägermaterial • Tela di supporto • Tela de soporte

woven

Width

Breedte • Largeur
Breite • Altezza • Ancho

± 400 & 500 cm

Effective pile height

Nuttige poolhoogte • Hauteur de velours utile
Tatsächliche Florhöhe • Spessore felpa utile • Altura de pelo

± 5,5 mm

Total height

Totale dikte • Hauteur totale
Gesamthöhe • Spessore totale • Altura total

± 8,0 mm

Number of knots/sqm

Aantal noppen/m² • Nombre de points/m²
Noppenzahl/m² • Numero di punti/mq • Puntos de pelo/m²

± 252.000

Pile weight/sqm

Poolinzetgewicht/m² • Poids mis en oeuvre/m²
Poleinsatzgewicht/m² • Peso felpa/mq • Peso de pelo/m²

± 1.540 gr

Total weight/sqm

Totaal gewicht/m² • Poids total/m²
Gesamtwicht/m² • Peso totale/m² • Peso total/m²

± 2.510 gr

EN 13501-1 Fire behaviour

Brandgedrag • Comportement au feu
Brennverhalten • Reazione al fuoco • Resistencia al fuego

B_{fl}-s1

EN 1307-2004 Classification

Classificatie • Classification
Klassifizierung • Classificazione • Clasificación al uso

Class 32

Commercial General

ISO 140/8 1997 Impact sound insulation

Contactgeluidsisolatie • Isolation aux bruits d'impact
Trittschallverbesserungsmaß • Miglioramento acustico • Aislamiento acústico

± 25 dB

DIN 52612 Thermal retention

Warmtedoorlaatweerstand • Résistivité thermique
Wärmedurchlaßwiderstand • Resistenza termica • Resistencia térmica

± 0,08 m²/kW

TOG Rating

± 0,8

ISO 105 B02 2000 Lightfastness

Lichtechtheid • Solidité à la lumière
Lichtechtheit • Solidità colori alla luce • Solidez del color a la luz

≥ 5

ISO 105 E01 2002 Waterfastness change in colour

Waterechtheid verkleuring • Solidité à l'eau changement couleur
Wasserechtheit Änderung der Farbe • Solidità colori all'acqua cambio colore
Solidez color al agua cambio de color

≥ 3-4

ISO 105 E01 2002 Waterfastness staining

Waterechtheid uitbloeding • Solidité à l'eau dégorgeement
Wasserechtheit anbluten • Solidità colori all'acqua sfumatura colore
Solidez color al agua pérdida de color

≥ 2-3

ISO 105 X12 2001 Rubbingfastness dry

Wrijfchtheid droog • Solidité au frottement sec
Reibungechtheit trocken • Solidità colori allo sfregamento a secco
Solidez del color a la frotación en seco

≥ 3-4

ISO 105 X12 2001 Rubbingfastness wet

Wrijfchtheid nat • Solidité au frottement humide
Reibungechtheit nass • Solidità colori allo sfregamento umido
Solidez del color a la frotación en húmedo

≥ 3

(4) These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to improve technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet. For other languages see: www.lano.com



Venetiaalaan 33 • 8530 Harelbeke-Belgium
t +32-56-65 40 00
marketing@lano.be • www.lano.com